RENDERING FAÇAD





Project 1 Rendering façades

Real estate is more valuable than ever today. It is therefore all the more important to preserve buildings. And the façade is a good place to start. It is the building's business card. It should always look good and must be afforded optimum protection against all weathers all year round. KRAUTOL renderings give buildings reliable protection and elegance. The KRAUTOL range includes a render for every requirement and to professional quality standards from the DAW Group.

The KRAUTOL system solution



WP QUARZ PUTZGRUND RENDERING BASE



DROPAN PLUS SILICONHARZPUTZ SILICONE RESIN RENDERING







First check the façade and its preparatory render coat. The existing render subsurface must be smooth, stable, firmly bonded and undamaged across its whole breadth. Remove any loose patches and repair. Clean the façade with a pressure washer and completely remove any dirt. Allow façade to dry out thoroughly after cleaning — 1 to 3 days, depending on weather conditions.



Prime subsurface with **WP-QUARZ**. A high-grade rendering base ensures optimum adhesion and uniform drying for the subsequent layer of render. Allow facade to dry thoroughly again after priming.



Rendering

Apply **DROPAN PLUS SILICONHARZPUTZ** upwards into the grain with the smoothing trowel to ensure maximum protection.



Texture

Use the plastic trowel to give a textured finish. Always work wet render into wet render. Allow façade to dry for at least 3 days after the rendering is applied.



Do not work in blazing sun or on heated subsurfaces; otherwise, ridges will emerge if rendering dries quickly.



Stainless steel smoothing trowel; plastic trowel; long-pile, padded façade roller (for applying subsequent paint coat).

When using the recommended products, please observe our further product, processing and safety instructions found on the product packaging and our technical info sheets, available from our website at www.kroutol.de.

Our suggestions are standard solutions for a variety of applications. They are based on our extensive experience as a paint manufacturer. We recommend obtaining professional advice if you wish to apply coating to objects under special conditions.



You will find more information and projects here

06/2016