



Project 4Shaping interior plaster

Rendering gives interior walls and façades a characteristic texture. Decorative interior plasterwork impresses due to its multiple design possibilities.

KRAUTOL EASY RAPID FEINPUTZ makes interiors quick and easy to design. Finishing render is applied with a roller and can be easily custom-shaped with a brush or palette-knife.

Note: KRAUTOL EASY RAPID FEINPUTZ can be tinted in a mixing machine to provide colour wall designs. KRAUTOL offers a whole variety of harmonious colours.

The KRAUTOL system solution



PRIMFR PAINT



FINISHING RENDER



KRAUTOL®

Shaping interior plaster



Check and prime subsurface

The surface must be smooth, firm, non-sanding and non-chalking.

Remove any peeling coatings and loose wallpaper.

Prime wall surface with **WP-UNI**. This product regulates absorption behaviour and guarantees optimum handling and results. Leave to dry for 12 hours after applying the coat.



Roll on

Use the roller to freely apply EASY RAPID FEINPUTZ vertically and horizontally in a criss-cross motion. Work from top to bottom in strips about 1 metre wide.



Shaping

Use EASY RAPID FEINPUTZ to shape render as you wish easily with a roller, brush or palette-knife. Always work wet render into wet render — best if two people work together.



Comb through new rollers to ensure no fluff gets into the plaster.

Dampen the roller before use.

Try out desired texture in advance: use a 1 m² sample surface first, for example.



Short-pile roller for extra fine finishing render, medium-pile roller with fibres between 14 and 18 mm high for finishing render; to texture: roller, brush or palette-knife.

When using the recommended products, please observe our further product, processing and safety instructions found on the product packaging and our technical info sheets, available from our website at www.kroutol.de.

Our suggestions are standard solutions for a variety of applications. They are based on our extensive experience as a paint manufacturer. We recommend obtaining professional advice if you wish to apply coating to objects under special conditions.

